

## LDC - RM-ARROW

### LDC - RM-A Roof Mounted Arrow Sign

#### UNIQUE FEATURES

**Low Total Cost of Ownership** - The Arrow Boards are designed for lowest total cost of ownership. Arrow Boards are constructed from small, inexpensive, easy to replace parts.

**Dual Circuit Pixels** - Each Pixel is made from 2 circuits providing redundancy. If an LED fails or is damaged, the message remains readable.

**LDC's LED Arrow Boards** - have been designed for ease of use and low cost of ownership.

These units have been tested to comply with AS4192 - 2006 and feature the lowest power consumption of any arrow board of this type. They are compatible with both 12V and 24V vehicle systems and have a discreet, easy to use controller which automatically raises and lowers the arrow board with a single control.

#### STANDARD FEATURES

- Auto Brightness - The Arrow Board automatically adjusts the LED brightness to suit ambient light conditions.
- Lowest power consumption of any AS4192 compliant Arrow Board. Uses less than 1 Amp average for single B size arrow.
- AS4192 - 2006 Compliant.
- Left Arrow - Right Arrow - Double Arrow - Non Directional Warning
- Small, easy to use in-cab controller.
- Single or Double sided options
- Low profile
- Lightweight
- Operates from 12 or 24V systems without voltage converters
- LED's have a 50,000+ hour life expectancy



Arrow right



#### In-Cab Controller -

Small, easy to use in-cab controller, mounts in standard dashboard spare switch position.

#### OPTIONS

**Electric Actuator** - Automatic raising and lowering.



Arrow left

**LED Arrow Boards**  
(Available in A and B sizes)